

Touring High Tech Tropical Motoroil 20W-50

Description

Touring High Tech Tropical SAE 20W-50 is an all season, high-performance motor oil formulated using state-of-the-art technology. Selected base oils and a high additive content ensure optimum lubrication under extreme operating conditions and during long periods between oil changes.

Properties

- guarantees low oil consumption
- can be used in gasoline and diesel engines with and without turbocharger
- prevents black sludge
- very good dispersion properties
- oil film strength
- high shear stability
- low evaporation loss
- excellent cleaning effect
- mixable with all commercially available motor oils
- tested for catalytic converters
- universal application
- excellent wear resistance
- optimum stability to aging

Specifications and approvals:

ACEA A3 • ACEA B4 • ACEA E7 • API SL • API CH-4 • Mack EO-M Plus

LIQUI MOLY recommends this product for vehicles for which the following specifications are required:

MAN M 3275-1 • MB 228.3

Technical data

SAE class (engine oils)	20W-50 SAE J300
Density at 15 °C	0,890 g/cm ³ DIN 51757
Viscosity at 40 °C	165 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	19,5 mm ² /s ASTM D 7042-04
Viskosität bei -20°C (MRV)	< 60000 mPas ASTM D4684
Viskosität bei -15°C (CCS)	<= 9500 mPas ASTM D5293
Viscosity index	136 DIN ISO 2909
HTHS bei 150°C	>= 3,5 mPas ASTM D5481



Technical data

Pour point	-30 °C DIN ISO 3016
Evaporation loss (Noack)	6,5 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	8,5 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	4,0 DIN ISO 2049

Areas of application

Universal motor oil for gasoline and diesel engines (aspirated diesel engines and diesel engines with exhaust gas turbocharging, with and without charge air cooler). Especially suitable where there are long intervals between oil changes and extreme operating conditions.

Application

The operating instructions of the vehicle and engine manufacturers must be followed.

Available pack sizes

1 l Canister plastic	2920 D-GB-I-E-P
4 l Canister plastic	2921 D-GB-I-E-P
5 l Canister plastic	2132 D-GB-I-E-P
205 l Drum sheet metal	2118 D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.